


Advancing Cancer Diagnostics
Improving Lives



Leica TP1020

Automatic Tissue Processor for the Histology Laboratory



Reliable Technology, Maximum Specimen Safety

Leica sets new standards in many fields of application with technically innovative instruments for specimen preparation. The Leica TP1020 is an automatic tissue processor that perfectly combines approved technology with modern, user-friendly design. Gentle specimen processing and maximum safety for tissue at all stages of the processing run, robust engineering design based on innovative precision mechanics in conjunction with a modern user interface – these are the convincing features of the Leica TP1020. Easy to program, this instrument offers the user utmost flexibility to suit the individual requirements of any laboratory.


Reduced exposure to hazardous fumes

The instrument variation with fume control system offers two options for removing solution fumes:



- The use of two different activated carbon filters (for formalin and alcohol/xylene) frees the exhaust air from the solution fumes and releases the cleansed air into the ambient atmosphere.
- An exhaust air tube directs the solution fumes to an outlet.

The efficiency of the system is further enhanced by a two-part plexiglass fume containment shield surrounding the reagent container platform.



Tissue infiltration under vacuum

Vacuum can be applied to any of the stations both in manual and automatic operation. The advantage: substantially improved infiltration of tissue in a shorter time. Instruments with the vacuum feature are equipped with anodized aluminum containers.



Maximum safety for the tissue

The tissue specimens are protected from drying out even during a power failure since the tissue baskets are automatically immersed in a station. The program is resumed where interrupted once mains power is restored. After a long-term power failure, the wax will be liquefied.

If the programmed infiltration time for any of the stations is exceeded a warning message is displayed indicating the station number and the time in excess of program.



User-friendly, easy-to-use control panel

The buttons of the control panel are arranged in functional groups. The easy-to-read LCD indicates the station parameters such as number of tissue baskets, vacuum function and remaining infiltration time, real time, start time (delayed start), overall duration and end of run time. Each of the nine programs can be run with immediate or delayed start.

Practical details


The specimen throughput can be doubled by using a second tissue basket for improved productivity in routine and research laboratories. The tissue basket is moved up and down in the liquid at three-second intervals to ensure thorough and even mixing of the reagents and optimum infiltration of the tissue. Sealing rings on the container lids reduce solution loss and therefore also emission into the ambient atmosphere to a minimum.

All reagent stations are easily accessible because the instrument can be



rotated nearly immediately and without difficulty by using the integrated and adjustable rollers.

Four configurations are available: basic instrument; base instrument with vacuum; base instrument with fume control system; and base instrument with vacuum and fume control.



Leica TP1020 with vacuum and fume control

Wide range of accessories:

- Glass beakers with beaker carriers
- Anodized aluminum container with beaker carriers
- Teflon coated wax bath



- Three-part tissue basket with lid (for organized loading of cassettes)
- Standard tissue baskets
- Basket removal device with drip tray



Outstanding Product Features

- › Carousel type with 12 stations
- › Configurations:
 - Basic instrument
 - Vacuum function
 - Fume control system
 - Vacuum function with fume control system
- › Option: two basket loading
- › Tissue baskets made of metal with varying capacities of up to 100 cassettes
- › Ergonomic control panel with foil-protected keyboard and LCD
- › Infiltration time separately programmable for each station
- › Delayed start function up to 9 days
- › Possibility of interrupting an automatic process for reloading or removing cassettes for special applications before the end of a run
- › Easy editing and changing of programs, even during a processing run
- › Audible alarms, error messages and warning codes
- › Advanced safety concept
- › Wide range of accessories

Up-to-date development, production and quality control procedures certified under DIN EN ISO 9001 ensure highest quality and reliability.

LEICA BIOSYSTEMS

Leica Biosystems is a global leader in workflow solutions bringing histopathology laboratories and researchers the highest quality, most comprehensive product range in anatomical pathology. With complete histology systems featuring innovative automation, Novocastra™ reagents and Surgipath® consumables, Leica Biosystems offers the ideal product for each histology step and high-productivity workflow solutions for the entire laboratory.

Leica Biosystems – an international company with a strong network of worldwide customer services:

North America Sales and Customer Support

North America	800 248 0123
---------------	--------------

Asia/Pacific Sales and Customer Support

Australia	1800 625 286
China	+85 2 2564 6699
Japan	+81 3 5421 2804
South Korea	+82 2 514 65 43
New Zealand	0800 400 589
Singapore	+65 6779 7823

Europe Sales and Customer Support

For detailed contact information about European sales offices or distributors please visit our website.

Technical Specifications

Electrical specifications:

Nominal voltage: _____ 100 / 120 / 230 / 240 V AC ±10%

Nominal frequency: _____ 50 / 60 Hz

Dimensions:

Carousel lid: _____ 820 mm Ø

Height: _____ 595 – 780 mm

Diameter of rollers: _____ 610 mm

Dry weight (including accessories): _____ 60 kg

Wax baths:

Number: _____ 2 (3 optional)

Capacity: _____ 1.8 l

Temperature range: _____ 45 °C – 65 °C

Excess temperature cutout: _____ 75 °C ± 4 °C

Reagent containers:

Number: _____ 10 (9)

Capacity: _____ 1.8 l

Standard tissue basket:

Number: _____ 1 (2 optional)

Capacity: _____ max. 100 cassettes

Programs:

Number: _____ 9, freely selectable

Programmable infiltration time per station: _____ 99 h 59 min

Delayed start: _____ 9 days

Drain time: _____ 60 s

Vacuum device (depending on the configuration):

Pressure difference: _____ max. 500 hPa (approx. 0.5 bar)

Leica Biosystems brings together products, quality and support. Offering a complete solution that helps you advance workflows, enhance diagnostic clarity and deliver what really matters – better patient care.

